

DHI-LM32-E230C

31.5" FHD Monitor



Features:

Power Type

- The 1920*1080 resolution produces clearer and more vivid pictures;
- · Comfortable 1500R exquisite curvature, close to the natural look and feel of the human eye, bringing immersive visual
- · Wide color gamut, 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB. It meets the designer's demand of image
- · 178°H/178°V extra-wide viewing angle for all-round viewing performance;
- · Adaptive sync can effectively solve picture lagging and tearing problems;

Duild in nower

· 1ms fast response time with no image blurring or ghosting;

Technical Specification

М	od	el
1 V I	Ou	\sim 1

Display Screen Size 31.5" Panel type VA Aspect Ratio 16:9 Resolution 1920x1080 Backlight E-LED Brightness/Luminance 300nits(typ) Contrast Ratio 3000:1 Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max) Refresh Rate 165Hz (max)
Panel type VA Aspect Ratio 16:9 Resolution 1920x1080 Backlight E-LED Brightness/Luminance 300nits(typ) Contrast Ratio 3000:1 Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Aspect Ratio 16:9 Resolution 1920x1080 Backlight E-LED Brightness/Luminance 300nits(typ) Contrast Ratio 3000:1 Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Resolution 1920x1080 Backlight E-LED Brightness/Luminance 300nits(typ) Contrast Ratio 3000:1 Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Backlight E-LED Brightness/Luminance 300nits(typ) Contrast Ratio 3000:1 Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Brightness/Luminance 300nits(typ) Contrast Ratio 3000:1 Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Contrast Ratio 3000:1 Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Color Support 99% sRGB, 85% NTSC, 85% DCI-P3, 85% Adobe RGB Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Viewing Angle(H/V) 178°(H)/178°(V) Response time MPRT 1ms (max)
Response time MPRT 1ms (max)
Refresh Rate 165Hz (max)
Signals
Interface DP1.2×1, HDMI 1.4×2, Audio out×1
General
Power Supply AC 100-240V~ 50/60Hz 1.5A

Power Type	Build in power		
Consumption (Standard)	TYP. 45W, MAX. 72 W		
Consumption (Standby)	<0.5W		
Net Weight	6.99kgs		
Gross Weight	9.04kg		
Tilt Angles	-5°±2°/15°±2°		
Swivel(angle)	N/A		
Pivot(angle/direction)	N/A		
Height Adjustment	N/A		
VESA	75x75mm		
Dimension(W×H×D)	712.5*422.8*120.6mm(without stand)		
Package(W×H×D)	801*171*533mm		
Work Environment	Temperature	0°~40°(32°F~104°F)	
	Humidity	10%~85%	
Accessory			
Standard	DP cable,Power cable,Stand,Base		