

DHI-LM43-F400

Dahua 43-inch UHD Monitor



- 4K Ultra-HD resolution.
- IPS panel, suitable for continuous 24/7 operation.
- Ultra-narrow bezel design, elegant appearance.
- 178°H/178°V extra-wide viewing angle for overall viewing performance.
- High fidelity digital processing for a brilliant and vivid video.
- 8ms response time for no motion blur, judder or ghosting.
- Supports multiple signal interfaces including HDMI, VGA, USB, etc.
- Built-in speaker.



Response Time	8 ms
Lifespan	30000 hrs
Operation Hours	7 × 24 H
Surface Treatment	Haze 1%, 3H
Flicker-free Technology	Yes

Device Ports

Input Port	2 × HDMI 2.0 (3840 × 2160@60 Hz), 1 × VGA(1920 × 1080@75 Hz), 1 × USB 2.0, 1 × audio in, 1 × RS-232 in
Speaker	2 × 10 W

Power & Environmental Conditions

Power Supply	100–240 VAC (±10%), 50/60 Hz
Power Type	Built-in Power
Power Consumption	48 W (basic), 117 W (typ.), 120 W (max)
Standby Power Consumption	<0.5 W
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Operating Humidity	10%–80% (RH)
Storage Temperature	–20 °C to +60 °C (–4 °F to +140 °F)
Storage Humidity	5%–90% (RH)

General

Product Dimensions	957 mm × 557.1 mm × 94.4 mm (37.68" × 21.93" × 3.72") (W × H × D) without base
Package Size	1055 mm × 645 mm × 141 mm(41.54" × 25.39" × 5.55") (W × H × D)
Frame Width	U/L/R/D: 1.0 mm/1.0 mm/1.0 mm/17.9 mm (0.04"/0.04"/0.04"/0.70")
Net Weight	6.8 kg (14.88 lb)

Gross Weight	9.9 kg (21.83 lb)
Casing Color	Black
Control Mode	Five-button /Remote Control
Status Indicator Light	Yes
Wall Mount VESA	200 mm x 200 mm (7.87" x 7.87")
Accessory	Power cable, base, HDMI cable, user manual (QR code), QSG, legal and regulatory information, etc.

Certification

Certifications	CE EMC, CE LVD, CE ERP
----------------	------------------------

Ordering Information

Type	Model	Description
LED Monitor	DHI-LM43-F400	Dahua 43-inch UHD Monitor

Dimensions (mm[inch])

