

DHI-LM75-S400

75" UHD LED Monitor



Features :

- 4K Ultra-HD resolution
- Anti-glare panel, suitable for continuous 24/7 operation
- 178°/178° extra-wide viewing angle for overall viewing performance
- High fidelity digital processing for a brilliant and vivid video
- 8ms response time for no motion blur, judder or ghosting
- Support HDMI, DP, VGA and other signal input
- Built-in speaker
- Infrared remote control



Technical Specification

Model

| | |
|-------|---------------|
| Model | DHI-LM75-S400 |
|-------|---------------|

Display

| | |
|-------------------|-----------------------------|
| Screen Size | 75" |
| Aspect Ratio | 16:9 |
| Panel Type | IPS |
| Resolution | 3840×2160 (UHD) |
| Backlight | LED |
| Brightness | 350 cd/m ² (max) |
| Contrast Ratio | 1200:1 |
| Display Color | 1.07G (8bit+FRC) |
| Viewing Angle | 178°(H)/178°(V) |
| Response Time | 8ms |
| Refresh Rate | 60Hz |
| Surface Treatment | Haze 25%, 3H |

Signals

| | |
|---------|--|
| Input | HDMIx2, DPx1, VGAX1, USBx1, Audiox1, RS232(RJ45)x1 |
| Output | RS232(RJ45)x1 |
| Speaker | 10Wx2 |

General

| | |
|--------------|----------------------|
| Power Supply | AC 100~240V, 50/60Hz |
|--------------|----------------------|

| | | |
|-----------------------------|---|-----------------------|
| Power Consumption | 300W (typ.), 340W (max) | |
| Power Consumption (Standby) | <0.5W | |
| Net Weight | 36.5 kg (80.47 lb) | |
| Gross Weight | 52 kg (114.64 lb) | |
| VESA | 600x400mm | |
| Product Dimension (W×H×D) | 1,706.6 mm × 984.7 mm × 78.7 mm (76.88" × 38.77" × 3.10"), without wall-mount bracket | |
| Package Dimension (W×H×D) | 1,882 mm × 1,160 mm × 245 mm (74.09" × 45.67" × 9.65") | |
| Work Environment | Temperature | 0 C~40 C (32°F~104°F) |
| | Humidity | 10%~80% |

Accessory

| | |
|----------|---|
| Standard | HDMI cable, power cable, remote control, wall-mount bracket |
|----------|---|

Certifications

| | |
|----------------|----|
| Certifications | CE |
|----------------|----|

