

# DH-PFS3005-5GT


Unmanaged Desktop Switch



- Plug and play: No configuration required
- Robust design: 24/7 stable performance in operating temperature from 0°C to 40°C
- Optimized performance: Provides full-speed transmission in all ports simultaneously
- Flexible deployment: Supports desktop and wall mount



Plug & Play



Robust Design



Optimized Performance



Easy Installation

## Functions

### Full Gigabit Ports

Equipped with 5 10/100/1000 Mbps ports enable fast transmission for your network, ideal for home and small office scenario.

### Silent Operation

Designed with durable metal casing and fanless structure, ensure the heat dissipation during a noiseless operation.

### Easy Installation

Both deployment and settings are designed to make a hassle-free experience for our customers, while providing an optimal operation.

## Scene



Home



Shop



Dormitory



Meeting Room

## Technical Specification

### Performance

Layer	Layer 2
-------	---------

### Hardware

Standard Power Supply	Yes
Ethernet Port	4
Ethernet Port Rate	1000 Mbps
Power Supply	5V/600mA DC
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Operating Humidity	10%–90% (RH)
Storage Temperature	-20°C to +70°C (-4°F to +158°F)
Storage Humidity	10%–90% (RH)
Power Consumption	< 3W

### Performance

Switching Capacity	10 Gbps
Packet Forwarding Rate	7.44 Mpps
Packet Buffer Memory	1 Mbit
MAC Table Size	2K
Standards Compliance	IEEE 802.3; IEEE 802.3u; IEEE 802.3x; IEEE802.3az

### General

ESD	Air discharge: 8kV Contact discharge: 6kV
Thunderproof	Common mode: 2kV
Net Weight	195 g (0.43 lb)
Dimensions	100 mm × 65 mm × 22.6 mm (3.94" × 2.56" × 0.88") (L × W × H)

## Dimensions (mm[inch])

